IMPACT COLLECTION LINEATIONS

LCT® FIRST Luxury Carpet Tiles

Manufacturing process	Méthode de fabrication	Herstellungsverfahren	Fabricatiemethode
Tufting 1/10" loop pile	Tuftée 1/10" poil bouclé	Getuftet 1/10" Schlingenpol	Getuft 1/10" lussenpool
Pile content	**Composition du velours**	**Polmaterial**	**Poolsamenstelling**
100% PP Stainsafe®	100% PP Stainsafe®	100% PP Fleckweg®	100% PP Stainsafe®
Pile weight	**Poids du velours**	**Polgewicht**	**Poolgewicht**
Ca. 550 g/m²	Ca. 550 g/m²	Ca. 550 g/m²	Ca. 550 g/m²
Total weight	**Poids total**	**Gesamtgewicht**	**Totaal gewicht**
Ca. 4.300 g/m²	Ca. 4.300 g/m²	Ca. 4.300 g/m²	Ca. 4.300 g/m²
Pile height	**Hauteur du velours**	**Florhöhe**	**Poolhoogte**
Ca. 5 mm	Ca. 5 mm	Ca. 5 mm	Ca. 5 mm
Total height	**Hauteur totale**	**Gesamthöhe**	**Totale hoogte**
Ca. 7 mm	Ca. 7 mm	Ca. 7 mm	Ca. 7 mm
Tuft density	**Nombre de touffes**	**Noppenzahl**	**Aantal noppen**
Ca. 189.120/m²	Ca. 189.120/m²	Ca. 189.120/m²	Ca. 189.120/m²
Size	**Dimensions**	**Abmessung**	**Afmetingen**
50 x 50 cm	50 x 50 cm	50 x 50 cm	50 x 50 cm
Packaging	**Emballage**	**Verpackung**	**Verpakking**
5 m²	5 m²	5 m²	5 m²
Antistatique	**Antistatique**	**Antistatisch**	**Antistatisch**
< 2 kV	< 2 kV	< 2 kV	< 2 kV
Fire class	**Classement feu**	**Brandverhaltensklasse**	**Brandklasse**
C_{FL}-s1 (EN 13501-1)	C_{FL}-s1 (EN 13501-1)	C_{FL}-s1 (EN 13501-1)	C_{FL}-s1 (EN 13501-1)
Centexbel 0493-CPR-0130	Centexbel 0493-CPR-0130	Centexbel 0493-CPR-0130	Centexbel 0493-CPR-0130
Sound insulation	**Isolation aux bruits d'impact**	**Trittschalldämmung**	**Geluidsisolatie**
22 dB	22 dB	22 dB	22 dB
Fastness to light	**Solidité à la lumière**	**Lichtechtheit**	**Lichtechtheid**
5-6	5-6	5-6	5-6
Water fastness	**Solidité à l'eau**	**Wasserechtheit**	**Waterechtheid**
4-5	4-5	4-5	4-5

EN 14041

CE

16

Balta Industries - Wakkensteenweg 2
BE - 8710 Sint-Baafs-Vijve

DOP: 1010#BI0ACL

Textile Floor Covering EN 1307
Notified body 0493

C_{FL}-s1 | DL PCP | NA HCHO | DS

www.baltamediabank.com

REG.NR 90CF84A0
www.pro-dis.info

7 YEAR LIFE WEAR PROMISE | 10 YR STAIN STAINSAFE® PROMISE | EASY TO CLEAN BLEACH SAFE

StainSafe® www.stain-safe.com

ÉMISSIONS DANS L'AIR INTÉRIEUR A+ (A+ A B C)

EAC

balta carpet tiles

MAINTENANCE: Spillage should be taken up promptly and surface stains removed by an appropriate method as soon as possible. In heavy traffic areas the carpet should be cleaned daily with a vacuum cleaner. Periodic maintenance should be carried out by professional cleaning staff using appropriate extraction systems.
COLOUR MARCHING: As with all textile products there will be a variance in shade from batch to batch. Any samples supplied are as close a representation to the actual carpet as the production process will allow. An exact colour match between different dye batches cannot be guaranteed.

Balta Carpet Tiles • Zevensterrestraat 21 • B-9240 Zele • Tel. +32 (0)52 80 80 80 • www.baltagroup.com

02/2020

IMPACT COLLECTION LINEATIONS

LCT FIRST Luxury Carpet Tiles







▲ 380



▲ 880



▲ 900



▲ 980